


### Characteristics



Hydrocart



Activated Carbon



Corrosive  
Recovery



Accessories  
Included



Wear Protective  
Clothing (PPE)



Wet Recovery



- Can be used in the Pharmaceutical industry when equipped with a Stainless Steel SAE 304 4-Wheel Dolly or Tilting-Cart
- Designed for the Recovery of Acids and Corrosive Liquids
- Bypass Heavy Duty motor
- Available with a variety of activated carbon including KINA 3® activated carbon for the adsorption of Chloride and acid vapors (HF, HCL, etc). Other types of carbon available. Carbon cartridges must be ordered separately (not included).
- For liquid recovery
- Acid-resistant polyethylene, nylon and pvc
- Available with a 4-wheel dolly, tilting cart or hydro-cart
- 4-wheel dolly and tilting cart available in stainless steel
- Includes a complete tool kit.

## Specifications

2D-ARU-15 SERIES	111429B	111429C	111429D	111429E	111430B	111430C
<b>Model Name</b>	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 (TC) MRAC	2D-ARU-15 STD (HY-C) MRAC	2D-ARU-15 STD (HY-C) MRAC
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric	Electric	Electric
<b>Voltage</b>	240 V	240 V	240 V	240 V	240 V	240 V
<b>Hertz</b>	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Single	Single	Single	Single	Single	Single
<b>Wattage</b>	1050 W	1050 W	1050 W	1050 W	1050 W	1050 W
<b>Power</b>	1 kW	1 kW	1 kW	1 kW	1 kW	1 kW
<b>Amperage</b>	5 amps.	5 amps.	5 amps.	5 amps.	5 amps.	5 amps.
<b>Air Flow</b>	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O
<b>Plug Type</b>	European	UK	Swiss	Chinese	European	UK
<b>Suction Inlet</b>	38 mm	38 mm	38 mm	38 mm	38 mm	38 mm
<b>Cart Type</b>	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)	Tilt Cart (TC)	Hydro Cart (HYC)	Hydro Cart (HYC)
<b>Filter Cleaning</b>	None	None	None	None	None	None
<b>Wet Recovery Capacity</b>	47.3 L	47.3 L	47.3 L	47.3 L	47.3 L	47.3 L
<b>Length</b>	69 cm	69 cm	69 cm	69 cm	124 cm	124 cm
<b>Width</b>	76 cm	76 cm	76 cm	76 cm	51 cm	51 cm
<b>Weight (Vacuum Only)</b>	48 kg.	48 kg.	48 kg.	48 kg.	113 kg.	113 kg.
<b>Height</b>	122 cm	122 cm	122 cm	122 cm	130 cm	130 cm
<b>Cord Length</b>	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m	10.6 m
2D-ARU-15 SERIES	111430D	111430E				
<b>Model Name</b>	2D-ARU-15 STD (HY-C) MRAC	2D-ARU-15 STD (HY-C) MRAC				
<b>Type (Powerhead)</b>	Electric	Electric				
<b>Voltage</b>	240 V	240 V				
<b>Hertz</b>	50 Hz	50 Hz				
<b>Phase</b>	Single	Single				
<b>Wattage</b>	1050 W	1050 W				
<b>Power</b>	1 kW	1 kW				
<b>Amperage</b>	5 amps.	5 amps.				
<b>Air Flow</b>	173 m <sup>3</sup> /h	173 m <sup>3</sup> /h				
<b>Vacuum Pressure</b>	2110 mm H <sub>2</sub> O	2110 mm H <sub>2</sub> O				
<b>Plug Type</b>	Swiss	Chinese				
<b>Suction Inlet</b>	38 mm	38 mm				
<b>Cart Type</b>	Hydro Cart (HYC)	Hydro Cart (HYC)				
<b>Filter Cleaning</b>	None	None				
<b>Wet Recovery Capacity</b>	47.3 L	47.3 L				

<b>Length</b>	124 cm	124 cm
<b>Width</b>	51 cm	51 cm
<b>Weight (Vacuum Only)</b>	113 kg.	113 kg.
<b>Height</b>	130 cm	130 cm
<b>Cord Length</b>	10.6 m	10.6 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



ARU STD Tools and Accessories - Included



Liquid Filter - Included



Activated Carbon Cartridge - Optional



2D-ARU-15 STD (HY-C) MRAC

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



Hydrocart



Activated Carbon



Corrosive Recovery



Accessories Included



Wear Protective Clothing (PPE)



Wet Recovery

## Specifications for 2D-ARU-15 SERIES

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type
2D-ARU-15 (TC) MRAC	111429B	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	European
	Dimensions: H122 cm x W76 cm x L69 cm    Weight: 48 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 (TC) MRAC	111429C	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	UK
	Dimensions: H122 cm x W76 cm x L69 cm    Weight: 48 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 (TC) MRAC	111429D	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	Swiss
	Dimensions: H122 cm x W76 cm x L69 cm    Weight: 48 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 (TC) MRAC	111429E	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	Chinese
	Dimensions: H122 cm x W76 cm x L69 cm    Weight: 48 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 STD (HY-C) MRAC	111430B	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	European
	Dimensions: H130 cm x W51 cm x L124 cm    Weight: 113 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 STD (HY-C) MRAC	111430C	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	UK
	Dimensions: H130 cm x W51 cm x L124 cm    Weight: 113 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 STD (HY-C) MRAC	111430D	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	Swiss
	Dimensions: H130 cm x W51 cm x L124 cm    Weight: 113 kg.									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										
2D-ARU-15 STD (HY-C) MRAC	111430E	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	173 m <sup>3</sup> /h	2110 mm H <sub>2</sub> O	Chinese
	Dimensions: H130 cm x W51 cm x L124 cm    Weight: 113 kg.									

Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.

Please note that specifications are subject to change without notice

## Technical Sheet for 2D-ARU-15 SERIES

### FILTERS AND ACCESSORIES - Included

Part #	Description
211749	LIQUID FILTER ASSEMBLY

### MAIN CLOTH FILTER FOR DRY RECOVERY - Optional

Part #	Description
211430	MAIN FILTER ASSEMBLY w/YELLOW GASKET w/RING #214279 FOR POLY TANKS

### ACTIVATED CARBON CARTRIDGE - Optional

Part #	Description
212200B	CARBON CARTRIDGE ASSEMBLY WITH 3mm CARBON (REGULAR)
212200C	CARBON CARTRIDGE ASSEMBLY WITH 3mm MERSORB ACTIVATED CARBON (FOR MERCURY VAPORS)
212200K	CARBON CARTRIDGE ASSEMBLY WITH 3mm KOGC3/KINA3 CARBON (FOR CHLORIDE VAPORS)
212200L	CARBON CARTRIDGE ASSEMBLY WITH 3mm A-3 CARBON (FOR ARSINE AND PHOSPHINE VAPORS)

### FLANGED RING ASSEMBLY WITH GASKET FOR MIDDLE RING. (Required when Activated Carbon Cartridge is not used) - Optional

Part #	Description
213673	FLANGED RING ASSEMBLY w/GASKET FOR 10/15/25 GALLON MODELS

### TOOLS AND ACCESSORIES - Included

Part #	Description
381337	FLEX-TUBE TR HOSE ASSEMBLY 1.5"(38mm) x 10'(3m) FOR USE w/ARU, w/PLASTIC FEMALE CAMLOCKS ON BOTH
381092	DRAIN HOSE ASSEMBLY 0.75"(19mm)x5'(1.5m) CLEAR HOSE WITH 0.75"(19mm) PVC FEMALE CAMLOCK
381351	WAND PVC DOUBLE BEND 54"(1.4m) FOR ARU WITH MALE CAMLOCK
381354	CREVICE NOZZLE ASSEMBLY FOR ARU, 12" (30.5cm), BLACK POLYPROPYLENE, WITH MALE CAMLOCK ON ONE END
381353	CREVICE NOZZLE ASSEMBLY FOR ARU, 36" (91cm), BLACK POLYPROPYLENE, WITH MALE CAMLOCK ON ONE END
381355	SQUEEGEE TOOL 14"(35.6cm) PVC WITH EPDM RUBBER BLADES FOR USE WITH ARU

### TOOLS AND ACCESSORIES - Optional

Part #	Description
381352	WAND ASSEMBLY 48"(1.2m) -NYLON FOR ARU
381380	FLOOR TOOL 14" (36cm) ABS WITH NYLON BRUSHES