

### Characteristics



Continuous Duty



Detachable Tank



Dry Recovery



HEPA Filter Available  
HEPA - Optional



ULPA Filter Available  
ULPA - Optional



Pharma Applications



Cleanroom Compatible



- HEPA Filter - Optional with an efficiency of 99.995% on 0.3 micron. Tested: IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- ULPA Filter - With an efficiency of 99.999% on 0.12 micron. Tested: IEST-RP-CC001. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility - Optional
- \*Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed to be attached to process machines and for general cleanup in the Food Industry
- Can also be used for the recovery of Tablets in the Pharmaceutical Industry.
- Continuous Duty Single or 3-Phase motor · mounted vertically
- Manual Filter Shaker (MFS) system.
- Available in a fixed or mobile unit
- For dry recovery only
- Available versions: Stainless Steel, White-Powder Coated, Stainless Steel & White-Powder Coated
- Vertical mounting for areas with space constraints.
- Equipped with 4 wheels for easy maneuverability

## Specifications

| CD-2600 CR (MFS) SERIES     | 111308B1                     | 111319B1                     | 111464B1                           | 111468B1                           |
|-----------------------------|------------------------------|------------------------------|------------------------------------|------------------------------------|
| <b>Model Name</b>           | CD-2600 CR (MFS) - P/C & S/S | CD-2600 CR (MFS) - P/C & S/S | CD-2600 CR (MFS) - STAINLESS STEEL | CD-2600 CR (MFS) - STAINLESS STEEL |
| <b>Type (Powerhead)</b>     | Electric                     | Electric                     | Electric                           | Electric                           |
| <b>TEFC Motor</b>           | Yes                          | Yes                          | Yes                                | Yes                                |
| <b>Voltage</b>              | 400 V                        | 400 V                        | 400 V                              | 400 V                              |
| <b>Hertz</b>                | 50 Hz                        | 50 Hz                        | 50 Hz                              | 50 Hz                              |
| <b>Phase</b>                | Three                        | Three                        | Three                              | Three                              |
| <b>Wattage</b>              | 2200 W                       | 3700 W                       | 2200 W                             | 3700 W                             |
| <b>Power</b>                | 2.2 kW                       | 3.7 kW                       | 2.2 kW                             | 3.7 kW                             |
| <b>Amperage</b>             | 6 amps.                      | 7.4 amps.                    | 6 amps.                            | 7.4 amps.                          |
| <b>Air Flow</b>             | 330 m <sup>3</sup> /h        | 340 m <sup>3</sup> /h        | 330 m <sup>3</sup> /h              | 340 m <sup>3</sup> /h              |
| <b>Vacuum Pressure</b>      | 3300 mm H <sub>2</sub> O     | 3560 mm H <sub>2</sub> O     | 3300 mm H <sub>2</sub> O           | 3560 mm H <sub>2</sub> O           |
| <b>VRV Setting</b>          | 2795 mm H <sub>2</sub> O     | 3050 mm H <sub>2</sub> O     | 2795 mm H <sub>2</sub> O           | 3050 mm H <sub>2</sub> O           |
| <b>Sound Level</b>          | 68 dB(A)                     | 68 dB(A)                     | 68 dB(A)                           | 68 dB(A)                           |
| <b>Plug Type</b>            | Not Included                 | Not Included                 | Not Included                       | Not Included                       |
| <b>Suction Inlet</b>        | 50 mm                        | 50 mm                        | 50 mm                              | 50 mm                              |
| <b>Cart Type</b>            | Carriage Base (CB)           | Carriage Base (CB)           | Carriage Base (CB)                 | Carriage Base (CB)                 |
| <b>Filter Cleaning</b>      | Manual Filter Shaker (MFS)   | Manual Filter Shaker (MFS)   | Manual Filter Shaker (MFS)         | Manual Filter Shaker (MFS)         |
| <b>Dry Recovery - Tank</b>  | 36 L                         | 36 L                         | 36 L                               | 36 L                               |
| <b>Length</b>               | 66 cm                        | 66 cm                        | 66 cm                              | 66 cm                              |
| <b>Width</b>                | 51 cm                        | 51 cm                        | 51 cm                              | 51 cm                              |
| <b>Weight (Vacuum Only)</b> | 112 kg.                      | 112 kg.                      | 112 kg.                            | 112 kg.                            |
| <b>Height</b>               | 191 cm                       | 191 cm                       | 191 cm                             | 191 cm                             |
| <b>Cord Length</b>          | 10 m                         | 10 m                         | 10 m                               | 10 m                               |

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



CD-2600 Next to average sized man



CD-2600 Rear View



CD-2600 with Recovery Tank removed



HEPA Filter - Optional

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



Continuous Duty



Detachable Tank



Dry Recovery



HEPA Filter Available  
HEPA - Optional



ULPA Filter Available  
ULPA - Optional



Pharma Applications



Cleanroom Compatible

## Specifications for CD-2600 CR (MFS) SERIES

| Name                               | Part Number                           | Voltage | Hertz | Phase | Wattage         | Power  | Amperage              | Air Flow              | Vacuum Pressure          | Plug Type    | Dry Recovery - Tank |
|------------------------------------|---------------------------------------|---------|-------|-------|-----------------|--------|-----------------------|-----------------------|--------------------------|--------------|---------------------|
| CD-2600 CR (MFS) - P/C & S/S       | 111308B1                              | 400 V   | 50 Hz | Three | 2200 W          | 2.2 kW | 6 amps.               | 330 m <sup>3</sup> /h | 3300 mm H <sub>2</sub> O | Not Included | 36 L                |
|                                    | Dimensions: H191 cm x W51 cm x L66 cm |         |       |       | Weight: 112 kg. |        | Sound Level: 68 dB(A) |                       |                          |              |                     |
| CD-2600 CR (MFS) - P/C & S/S       | 111319B1                              | 400 V   | 50 Hz | Three | 3700 W          | 3.7 kW | 7.4 amps.             | 340 m <sup>3</sup> /h | 3560 mm H <sub>2</sub> O | Not Included | 36 L                |
|                                    | Dimensions: H191 cm x W51 cm x L66 cm |         |       |       | Weight: 112 kg. |        | Sound Level: 68 dB(A) |                       |                          |              |                     |
| CD-2600 CR (MFS) - STAINLESS STEEL | 111464B1                              | 400 V   | 50 Hz | Three | 2200 W          | 2.2 kW | 6 amps.               | 330 m <sup>3</sup> /h | 3300 mm H <sub>2</sub> O | Not Included | 36 L                |
|                                    | Dimensions: H191 cm x W51 cm x L66 cm |         |       |       | Weight: 112 kg. |        | Sound Level: 68 dB(A) |                       |                          |              |                     |
| CD-2600 CR (MFS) - STAINLESS STEEL | 111468B1                              | 400 V   | 50 Hz | Three | 3700 W          | 3.7 kW | 7.4 amps.             | 340 m <sup>3</sup> /h | 3560 mm H <sub>2</sub> O | Not Included | 36 L                |
|                                    | Dimensions: H191 cm x W51 cm x L66 cm |         |       |       | Weight: 112 kg. |        | Sound Level: 68 dB(A) |                       |                          |              |                     |

Please note that specifications are subject to change without notice

## Technical Sheet for CD-2600 CR (MFS) SERIES

### HEPA/ULPA FILTERS AND ACCESSORIES - Optional

| Part #  | Description  |
|---------|--|
| 213182  | HEPA FILTER (H14) W/GASKET, Ø13.8125"(35.1cm)x3.875"(98.4mm) HIGH          |
| 213181  | ULPA FILTER (U15), Ø13.8125" x 3.875"(35.1cm X 98.4mm) HIGH, RATED 250 CFM |
| 215014B | HEPA HOUSING FOR CD-2600-STD, CRS -POWDER COATED                           |
| 215012  | HEPA HOUSING FOR CD-2600 -STAINLESS STEEL 304                              |

### FILTERS AND ACCESSORIES - Included

| Part #   | Description  |
|----------|--|
| 215025TA | MAIN FILTER WITH CLAMP -PTFE LAMINATED (SUPPORT RING AND CAGE SOLD SEPARATELY) |
| 214685A  | CAGE FOR FILTER FOR SS-10 (DT) MFS -ZINC PLATED                                |

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

| Part # | Description  |
|--------|--|
| 214987 | POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)                  |
| 213780 | POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP) |

| TOOLS AND ACCESSORIES - Optional |   |
|----------------------------------|---|
| Part #                           | Description   |
| 500390                           | CLEAR URETHANE SUCTION HOSE SD* Ø2"(50mm) LIGHT WEIGHT&ABRASION RESISTANT (SOLD PER FOOT)     |
| 635078                           | CLEAR URETHANE SUCTION HOSE SD* Ø2.5"(64mm) LIGHT WEIGHT & ABRASION RESISTANT (SOLD PER FOOT) |
| 500159                           | CLAMP, TRIDON (SCREW TYPE) SIZE 32 -STAINLESS STEEL   |
| 635016                           | HOSE CLAMP -STAINLESS STEEL SCREW TYPE FOR Ø2.5"(64mm)HOSE                                    |
| 500198                           | HOSE CUFF EXPANDER FOR Ø2"(50mm)VACUFLEX HOSE TO Ø2.5"(63.5mm)ADAPTOR (500168+635248)         |
| 500168                           | HOSE CUFF Ø2"(50mm) FOR Ø2"(50mm) VACUFLEX HOSE   |
| 635248                           | HOSE CUFF FOR Ø2.5"(64mm) WIRE SUPPORTED HOSE   |