

Characteristics



Cleanroom Compatible




Wet Recovery



ULPA - Included



High Efficiency



EMI Shielded



Activated Carbon



Corrosive Recovery



Accessories Included



Wear Protective Clothing (PPE)



- ULPA Filter - With an efficiency of 99.999% on 0.12 micron. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility - Included
- *Cleanroom compatible with ISO Class 4 (former Class 10)
- Designed for the Recovery of Acids and Corrosive Liquids
- EMI/RFI Shielded
- Bypass Heavy Duty motor
- Available with a variety of activated carbon including KINA 3® activated carbon for the adsorption of Chloride and acid vapors (HF, HCL, etc). Other types of carbon available. Carbon cartridges must be ordered separately (not included).
- For liquid recovery
- Acid-resistant polyethylene, nylon and pvc
- Includes a complete tool kit.

Specifications

CWR-ARU-15 (TC) POLY MRAC	110511B
Model Name	CWR-ARU-15 (TC) POLY MRAC
Type (Powerhead)	Electric
Voltage	240 V
Hertz	50 Hz
Phase	Single
Wattage	1050 W
Power	1 kW
Amperage	5 amps.
Air Flow	189 m ³ /h
Vacuum Pressure	2180 mm H ₂ O
Sound Level	75 dB(A)
Plug Type	European
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Wet Recovery Capacity	47.3 L
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



ULPA Filter - Included



Liquid Filter - Included



ARU STD Tools and Accessories - Included



Activated Carbon Cartridge - Optional



Cleanroom
Compatible




Wet Recovery



ULPA -
Included



High Efficiency



EMI Shielded



Activated
Carbon



Corrosive
Recovery



Accessories
Included



Wear Protective
Clothing (PPE)

Specifications for CWR-ARU-15 (TC) POLY MRAC

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type
CWR-ARU-15 (TC) POLY MRAC	110511B	240 V	50 Hz	Single	1050 W	1 kW	5 amps.	189 m³/h	2180 mm H2O	European
	Sound Level: 75 dB(A)									
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.										

Please note that specifications are subject to change without notice

Technical Sheet for CWR-ARU-15 (TC) POLY MRAC

FILTERS AND ACCESSORIES - Included

Part #	Description
211749	LIQUID FILTER ASSEMBLY

MAIN CLOTH FILTER FOR DRY RECOVERY - Optional

Part #	Description
211430	MAIN FILTER ASSEMBLY w/YELLOW GASKET w/RING #214279 FOR POLY TANKS

ACTIVATED CARBON CARTRIDGE - Optional

Part #	Description
212200B	CARBON CARTRIDGE ASSEMBLY WITH 3mm CARBON (REGULAR)
212200C	CARBON CARTRIDGE ASSEMBLY WITH 3mm MERSORB ACTIVATED CARBON (FOR MERCURY VAPORS)
212200K	CARBON CARTRIDGE ASSEMBLY WITH 3mm KOGC3/KINA3 CARBON (FOR CHLORIDE VAPORS)
212200L	CARBON CARTRIDGE ASSEMBLY WITH 3mm A-3 CARBON (FOR ARSINE AND PHOSPHINE VAPORS)

FLANGED RING ASSEMBLY WITH GASKET FOR MIDDLE RING. (Required when Activated Carbon Cartridge is not used) - Optional

Part #	Description
213673	FLANGED RING ASSEMBLY w/GASKET FOR 10/15/25 GALLON MODELS

TOOLS AND ACCESSORIES - Included

Part #	Description
381337	FLEX-TUBE TR HOSE ASSEMBLY 1.5"(38mm) x 10'(3m) FOR USE w/ARU, w/PLASTIC FEMALE CAMLOCKS ON BOTH
381092	DRAIN HOSE ASSEMBLY 0.75"(19mm)x5'(1.5m) CLEAR HOSE WITH 0.75"(19mm) PVC FEMALE CAMLOCK
381351	WAND PVC DOUBLE BEND 54"(1.4m) FOR ARU WITH MALE CAMLOCK
381354	CREVICE NOZZLE ASSEMBLY FOR ARU, 12" (30.5cm), BLACK POLYPROPYLENE, WITH MALE CAMLOCK ON ONE END
381353	CREVICE NOZZLE ASSEMBLY FOR ARU, 36" (91cm), BLACK POLYPROPYLENE, WITH MALE CAMLOCK ON ONE END
381355	SQUEEGEE TOOL 14"(35.6cm) PVC WITH EPDM RUBBER BLADES FOR USE WITH ARU

TOOLS AND ACCESSORIES - Optional

Part #	Description
381352	WAND ASSEMBLY 48"(1.2m) -NYLON FOR ARU
381380	FLOOR TOOL 14" (36cm) ABS WITH NYLON BRUSHES