

Characteristics



ULPA - Included



Continuous Duty




EX Certified



SS 304



Dry Recovery



Less than 10 ohms



- Legally certified explosion proof/dust ignition proof.
- Less than 10 Ohms of resistivity.
- ULPA Filter - With an efficiency of 99.999% on 0.12 micron. Filtration efficiency of 99.9995% on 0.18 micron. Tested: IEST-RP-CC001. U15 by MPPS method as per EN 1822. All of our ULPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility - Included
- Includes a muffler for noise reduction.
- Available with a Conductive Filter Bag (CFB) or Manual Reverse Purge with Filter Tubes (MRPFT) system
- Designed to be attached to process machines and for general cleanup
- Can also be used for the recovery of Tablets in the Pharmaceutical Industry.
- Continuous Duty Single Phase (TEFC) Explosion Proof/Dust Ignition Proof motor
- For dry recovery only
- All Stainless Steel SAE 304 construction
- Vertical mounting for areas with space constraints.
- SD* Polyliner and retainer clip included, for the easy and safe disposal of recovered materials.
- Includes a complete static dissipative tool kit
- Motor and switch for use in presence of conductive metal dusts available. North-America: Class II, Group E; Europe: Dust group IIIC
- Other motor performances available.

Specifications

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Ø1.5 (Ø38mm) Static Dissipative Tools and Accessories - Included



Collection Filter Bag (CFB), Static Dissipative



Filter Tubes Assembly for MRPFT models - Included



CD-230 EX (MRPFT) PHARMA

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



ULPA -
Included



Continuous
Duty



EX Certified



SS 304



Dry Recovery



Less than 10
ohms

Specifications for CD-230V EX PHARMA SERIES

Please note that specifications are subject to change without notice

Technical Sheet for CD-230V EX PHARMA SERIES

ULPA FILTER AND ACCESSORIES - Included	
Part #	Description
211027	ULPA FILTER (U15)

FILTERS AND ACCESSORIES FOR CFB MODELS - Included	
Part #	Description
215393TA-SD	MAIN FILTER ASSEMBLY w/LACES, EPITROPIC POLYESTER w/PTFE, FOR MODEL ATEX 22E (CAGE SOLD SEPARATELY)
218390	WIRE CAGE FOR CLOTH FILTER, STAINLESS STEEL TYPE 304

FILTER TUBES ASSEMBLY FOR MRPFT MODELS - Included	
Part #	Description
219150	SD* EPITROPIC POLYESTER w/PTFE FINGERS FILTER, ASSEMBLY
219154	CLOTH FINGERS FILTER, SD* EPITROPIC POLYESTER w/PTFE

PRE-FILTER FOR CFB MODELS - Optional	
Part #	Description
217707	PRE-FILTER ASSEMBLY SD* FOR LOWER HOUSING FOR CD-120 EX / CD-2000 EX

COLLECTION FILTER BAG (CFB) FOR CFB MODELS - Included	
Part #	Description
212994A-SD64	COLLECTION BAG MADE OF CONDUCTIVE MATERIAL (w/64mm COLLAR)

TOOLS AND ACCESSORIES - Included	
Part #	Description
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381364	DOUBLE BEND WAND ASSEMBLY (2pc) 1.5"(38mm) x 54"(137cm), STAINLESS STEEL w/ALUMINUM TOOL COUPLING
381236	UNIVERSAL TOOL SD* w/CONDUCTIVE BRUSH STRIPS, RUBBER BLADES, BRASS AXLE & WHEELS, 1.5" x18",ALUMINUM
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM
381185A	DUSTING BRUSH, SD*, WITH STAINLESS STEEL COUPLING, WITH CONDUCTIVE BRISTLES, 5"(12.5cm), ALUMINUM
383461D	CONICAL NOZZLE ASSEMBLY(STRAIGHT)7.5"(19cm)CONDUCTIVE RUBBER FOR HOSE CUFF WRING (383461M+381147D)

211065B	MULTIMETER
---------	------------

AVAILABLE UPGRADES - Optional	
--------------------------------------	--

Part #	Description
212779-M3EU	UPGRADE TO BALDOR MOTOR CL5030T-E, 1.5HP 120/230V 1PHSE FOR CLASS I -GRP D, CLASS II -GRPS E,F &G
218705	UPGRADE (FROM VIGANO) TO KILLRK B7MS1R BOX FOR (1HP TO 5HP) CLASS I-GROUP D, CLASS II-GRPOUS E,F & G