

### Characteristics



Coalescing Filter Element



SD Accessories - Included



SS 304




Dry Recovery




HEPA - Included



High Efficiency



Wet Mix - Water



Less than 10 ohms



- Dust Tight IP5X
- Immersion Separator "Wet (Water) Mix" - Only meant to be used with water (no oil).
- Designed for the recovery and INERTIZATION of combustible dust into a Liquid Immersion Bath
- Precipitating Dust - complies with NFPA 484 method
- Electrically Operated
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency on 0.3 microns
- Recovery tank made of stainless steel type 304
- Recovery capacity: 3.25 gallons (12.3 liters) of water is required in the recovery tank. The conductive "wet" recovery bag has a recovery capacity of 3 liters. One gallon (3.8 liters) of powder can be recovered directly in the tank if the conductive recovery bag is not used
- Degassing Vent allows gas to be evacuated automatically from the unit
- Equipped with a Liquid Level Indicator.
- Includes a complete static dissipative tool kit
- Brushless Motor available

## Specifications

2D-10 (IT-40L) CFE HEPA DUST TIGHT IP5X	113186B-3D
Model Name	2D-10 (IT-40L) CFE HEPA DUST TIGHT IP5X
Type (Powerhead)	Electric
Voltage	220/240 V
Hertz	50/60 Hz
Phase	Single
Wattage	1200 W
Power	1.2 kW
Amperage	5 amps.
Air Flow	194 m <sup>3</sup> /h
Vacuum Pressure	2504 mm H <sub>2</sub> O
Sound Level	75 dB(A)
Plug Type	Not Included
Suction Inlet	38 mm
Cart Type	4 Wheel Dolly (4W)
Filter Cleaning	Liquid Immersion Bath
Length	48 cm
Width	46 cm
Height	86 cm
Cord Length	10 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



Liquid Level Indicator and Drain Valve - Included



A Conductive "Wet" Recovery Bag can be used in conjunction with the Immersion Bath to facilitate material recovery and emptying



Coalescing HEPA filter (Upstream) - Included



Degassing Vent - Included



Static Conductive Suction Hose and Tool Kit - Included



Optional 3D Tools

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



Coalescing Filter Element



SD Accessories - Included



SS 304




Dry Recovery




HEPA - Included



High Efficiency



Wet Mix - Water



Less than 10 ohms

### Specifications for 2D-10 (IT-40L) CFE HEPA DUST TIGHT IP5X

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type
2D-10 (IT-40L) CFE HEPA DUST TIGHT IP5X	113186B-3D	220/240 V	50/60 Hz	Single	1200 W	1.2 kW	5 amps.	194 m <sup>3</sup> /h	2504 mm H <sub>2</sub> O	Not Included
	Dimensions: H86 cm x W46 cm x L48 cm    Sound Level: 75 dB(A)									

Please note that specifications are subject to change without notice

### Technical Sheet for 2D-10 (IT-40L) CFE HEPA DUST TIGHT IP5X

#### COALESCING FILTER ELEMENT - Included

Part #	Description
215792A-HEPA	REPLACEMENT COALESCING FILTER ELEMENT, HEPA GRADE, 4.75" HIGH, w/NITRILE GASKET #219259-04

#### MIST ARESTOR PACK - Included

Part #	Description
218282	MIST ARRESTOR SCREENS, MADE OF ALUMINUM MESH, FOR IT-40L (SET OF 6 SCREENS)

#### CONDUCTIVE RECOVERY BAG - Included

Part #	Description
219990A	CONDUCTIVE RECOVERY BAG FOR IT-40L - INSTALLED IN THE RECOVERY TANK
219990	CONDUCTIVE RECOVERY BAG FOR IT-40L (PACKAGE OF 3)

#### TOOLS AND ACCESSORIES - Included

Part #	Description
383440	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASSEMBLY(NO WIRE)Ø1.5"(38mm)x10'(3m) FOR 1.5" CAMLOCK IN
323312A	ROUND BRUSH, 1.25"(32mm) x 3"(7.5cm), ESD SAFE PLASTIC, WITH HOLE FOR BUTTON LOCK
381818	CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT
383462	CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)

#### TOOLS AND ACCESSORIES - Optional

Part #	Description
381477	DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS
381448A	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES

- A: Suction Intake
- B: Water
- C: Cooling Air Intake
- D: Cooling Air Exhaust
- E: Working Air Exhaust
- F: Degrassing Vent
- G: Drain Valve
- M: Motor

- 1: Conductive Recovery Bag
- 2: Mist Arrestor Pack
- 3: Coalescing Filter Element (Hepa Grade)

