

Characteristics



SD Accessories -
Included



HEPA - Included



High Efficiency




Dry Recovery



Coalescing Filter
Element



Stainless
General



Wet Mix - Water



- Dust Tight IP5X
- Coalescing Filter Element (CFE) for moisture removal. HEPA Grade. 99.97% efficiency on 0.3 microns
- Recovery capacity of 11 lbs (5 Kg) of dust into 6.5 gallons (25 liters) of water (no oil)
- Brushless Motor available

Specifications

2D-15 (IT-63L) CFE HEPA DUST TIGHT IP5X	113187B-3D
Model Name	2D-15 (IT-63L) CFE HEPA DUST TIGHT IP5X
Type (Powerhead)	Electric
Voltage	220/240 V
Hertz	50/60 Hz
Phase	Single
Wattage	1200 W
Power	1.2 kW
Amperage	5 amps.
Air Flow	194 m ³ /h
Vacuum Pressure	2504 mm H ₂ O
Sound Level	75 dB(A)
Plug Type	Not Included
Suction Inlet	50 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Liquid Immersion Bath
Length	79 cm
Width	61 cm
Weight (Vacuum Only)	82 kg.
Height	160 cm
Cord Length	10 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



2D-15 (IT-63L) with Recovery Tank removed



3D Toolkit - Included



Liquid Level Indicator Tube - Included



Mist Arrestor Pack - Optional



Optional 3D Tools



Coalescing HEPA filter (Upstream) - Included



Sieve Basket - Included



Cone for Interceptors - Included

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



SD Accessories - Included



HEPA - Included



High Efficiency




Dry Recovery



Coalescing Filter Element



Stainless General



Wet Mix - Water

Specifications for 2D-15 (IT-63L) CFE HEPA DUST TIGHT IP5X

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type
2D-15 (IT-63L) CFE HEPA DUST TIGHT IP5X	113187B-3D	220/240 V	50/60 Hz	Single	1200 W	1.2 kW	5 amps.	194 m ³ /h	2504 mm H ₂ O	Not Included
	Dimensions: H160 cm x W61 cm x L79 cm Weight: 82 kg. Sound Level: 75 dB(A)									
Description: Immersion Separator. Only meant to be used with water (no oil)										

Please note that specifications are subject to change without notice

Technical Sheet for 2D-15 (IT-63L) CFE HEPA DUST TIGHT IP5X

COALESCING FILTER ELEMENT - Included

Part #	Description
215792A-HEPA	REPLACEMENT COALESCING FILTER ELEMENT, HEPA GRADE, 4.75" HIGH, w/NITRILE GASKET #219259-04

MIST ARESTOR PACK - Optional

Part #	Description
218284	MIST ARRESTOR PACK ASSEMBLY (ALUMINUM SCREENS WITH STAINLESS STEEL MESH)

SIEVE BASKET AND ACCESSORIES - Optional

Part #	Description
218985	SIEVE BASKET WITH CLOSED BASE FOR IT-25, STAINLESS STEEL AISI 304

TOOLS AND ACCESSORIES - Included

Part #	Description
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381818	CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT
383312A	ROUND BRUSH ASSEMBLY, ESD SAFE PLASTIC, FOR USE WITH 1.5" (38mm) HOSE
383462	CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)

TOOLS AND ACCESSORIES - Optional

Part #	Description
381477	DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS
381448A	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES