

ATEX<sup>Ex</sup> CE II 2 GD  
Ex h IIC T6 Gb  
Ex h IIIC T85°C Db



**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts

**ESD Safe** Vacuum Cleaners for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

### Characteristics



EX Certified



Less than 10 ohms



Dry Recovery



HEPA - Included



High Efficiency



SS 304



- Legally certified explosion proof/dust ignition proof.
- Ideal for Medical/Dental 3D printer cleaning and maintenance
- Includes a complete static dissipative tool kit
- Low noise level: only 68 dB(A)
- Pressure regulator included. Pressure regulator is adjustable between 0 psi (0 bar) to 150 psi (10 bars). It is factory set at 80 psi (5.5 bars) for ideal performance and noise level

## Specifications

ATEX-10A (40L) HEPA W/3D TOOL KIT	113115
Model Name	ATEX-10A (40L) HEPA MINI SERIES
Type (Powerhead)	Pneumatic
Venturi	Single
Minimum Compressor	15 HP
Air Line Size (Diam.)	1/2" (12.7mm)
Input Air Volume	16.5-21.2 L/s
Input Air Pressure	5.5 Bar
Air Flow	187 m <sup>3</sup> /h
Vacuum Pressure	2790 mm H <sub>2</sub> O
Sound Level	68 dB(A)
Suction Inlet	38 mm
Cart Type	4 Wheel Dolly (4W)
Length	48 cm
Width	46 cm
Height	86 cm

Please note that specifications are subject to change without notice

### Use only recommended tools & accessories



Tools and Accessories - Included



Optional 3D Tools



Pressure Regulator - Included

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2


Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



CE II 2 GD  
Ex h IIC T6 Gb  
Ex h IIIC T85°C Db



EX Certified



Less than 10 ohms



Dry Recovery



HEPA - Included



High Efficiency



SS 304

**ESD Safe** Vacuum Cleaners for Hazardous Locations are designed to prevent ignition hazards.  
We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



**GUARANTEED** for the Safe Recovery of Combustible/Conductive Dusts

## Specifications for ATEX-10A (40L) HEPA W/3D TOOL KIT

Name	Part Number	Air Flow	Vacuum Pressure
<b>ATEX-10A (40L) HEPA MINI SERIES</b>	<b>113115</b>	187 m <sup>3</sup> /h	2790 mm H <sub>2</sub> O
Description: Specifications may vary depending upon performance of the compressor.			

Please note that specifications are subject to change without notice

## Technical Sheet for ATEX-10A (40L) HEPA W/3D TOOL KIT

### FILTERS - Included

Part #	Description
219046A	MAIN FILTER ASSEMBLY SD* FOR C-10 EX VACS WITH 4 LACES FOR WHITE FILTER CAGE (CAGE SOLD SEPARATELY)
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION

### CONDUCTIVE RECOVERY BAG - Included

Part #	Description
212994-SD	COLLECTION BAGS MADE OF CONDUCTIVE MATERIAL (PKG OF 3)

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Included

Part #	Description
212100S	CONDUCTIVE POLY LINER WITH DRAW STRING (40 LITRES/10 GALLONS)

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
212100S-5	CONDUCTIVE POLY LINER WITH DRAW STRING (40 LITRES/10 GALLONS)(PACKAGE OF 5)

### AIR SUPPLY HOSE - Included

Part #	Description
211029	AIR SUPPLY HOSE ASSEMBLY SD* 0.5"(12.7mm) x 25'(7.5m) w/1 MALE QUICK DISC. & 1 FEMALE QUICK DISC.

### TOOLS AND ACCESSORIES - Included

Part #	Description
383440D	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY 1.5"(38mm) x 10'(3m)FOR USE w/60mm CONDUCTIVE INLET

211029	AIR SUPPLY HOSE ASSEMBLY SD* 0.5"(12.7mm) x 25'(7.5m) w/1 MALE QUICK DISC. & 1 FEMALE QUICK DISC.
383312A	ROUND BRUSH ASSEMBLY, ESD SAFE PLASTIC, FOR USE WITH 1.5" (38mm) HOSE
381818	CREVICE TOOL 1.5"(38mm) x 8"(20cm) w/1.5" ALUMINUM TUBE, BLACK RUBBER, CONDUCTIVE & OIL RESISTANT
383462	CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)

#### TOOLS AND ACCESSORIES - Optional

Part #	Description
381477	DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS
381448A	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES