

Characteristics



HEPA - Included



High Efficiency



Wet and Dry
Recovery



- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001 H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- For general housekeeping
- Bypass Heavy Duty motor
- Middle Ring for Polyliner, for the recovery of wet/saturated asbestos.
- For wet and dry recovery
- Polyethylene recovery tank.
- Silent operation
- Mounted on a Tilting Cart (TC) for easy disposal of recovered materials.

Specifications

2D-16 (TC) RE HEPA MR (ASBESTOS)	110571B
Model Name	2D-16 (TC) RE HEPA MR (ASBESTOS)
Type (Powerhead)	Electric
Voltage	240 V
Hertz	50 Hz
Phase	Single
Wattage	1050 W
Power	1.1 kW
Amperage	5 amps.
Air Flow	173 m ³ /h
Vacuum Pressure	2110 mm H ₂ O
Sound Level	69 dB(A)
Plug Type	European
Suction Inlet	50 mm
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Dry Recovery - Tank	56.8 L
Wet Recovery Capacity	57 L
Length	69 cm
Width	69 cm
Weight (Vacuum Only)	39 kg.
Height	114 cm
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



HEPA Filter - Included



Main Cloth Filter - Included



Dralon Pre-Filter & Liquid Filter - Included



Asbestos Polyliner (6) W retaining clip (not shown) - Included



PVC Crushproof Suction Hose Assembly - Included



Conical Nozzle and Adaptor - Included

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



Specifications for 2D-16 (TC) RE HEPA MR (ASBESTOS)

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
2D-16 (TC) RE HEPA MR (ASBESTOS)	110571B	240 V	50 Hz	Single	1050 W	1.1 kW	5 amps.	173 m ³ /h	2110 mm H ₂ O	European	56.8 L
Dimensions: H114 cm x W69 cm x L69 cm Weight: 39 kg. Sound Level: 69 dB(A)											
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

Please note that specifications are subject to change without notice

Technical Sheet for 2D-16 (TC) RE HEPA MR (ASBESTOS)

HEPA FILTER AND ACCESSORIES - Included

Part #	Description
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)

FILTERS AND ACCESSORIES - Included

Part #	Description
211394	LIQUID FILTER ASSEMBLY
211430T	MAIN FILTER ASSEMBLY, PTFE LAMINATED, w/YELLOW GASKET, w/RING #214279 FOR USE WITH POLY TANKS

POLY LINER RECOVERY BAGS AND ACCESSORIES - Included

Part #	Description
212374	POLY LINER - NO PRINT (PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

PVC CRUSHPROOF SUCTION HOSE ASSEMBLY - Included

Part #	Description
500131	PVC CRUSHPROOF SUCTION HOSE ASSEMBLY Ø2"(50mm)x15'(4.5m) FOR Ø2"(50mm) CAMLOCK INTAKE

TOOLS AND ACCESSORIES - Included

Part #	Description
500230M	CONICAL NOZZLE 2"(50mm)x7.5"(19cm), STATIC CONDUCTIVE RUBBER
500620	ADAPTOR Ø2"(50mm)x5"(12.7mm) FOR CONICAL NOZZLE&TIGER CLAW -ALUMINUM

TOOLS AND ACCESSORIES - Optional

Part #	Description
500218	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), CHROME PLATED STEEL w/ TAPER FOR FLOOR TOOL
500220	FLOOR TOOL w/SQUEEGEE, 2" 50mm) x 20"(51cm), BLACK PLASTIC w/SWIVEL NECK w/ADJUSTABLE WHEELS
500222	ADAPTOR -BLACK PLASTIC (FOR USE WITH CREVICE TOOL/DUSTING BRUSH)

500224	CREVICE TOOL -BLACK PLASTIC
500226	DUSTING BRUSH -BLACK PLASTIC
501550	TOOL KIT #16 STANDARD ACCESSORIES - CUSTOM BUILT 2"(50mm)