

## Characteristics



Static  
Dissipating



HEPA - Included



Detachable Tank



Dry Recovery



SS 430



High Efficiency



- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001 H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- For general housekeeping
- Bypass Heavy Duty motor
- Manual Filter Shaker (MFS) system.
- For dry recovery only
- Stainless Steel Type 430 body and recovery tank.
- Detachable Recovery Tank (DT) for easy disposal of recovered materials
- Equipped with a 4-Wheel cart and tool basket. Cart has SD\* conductive wheels

## Specifications

2D-25L (DT) MFS HEPA	111402B	111402C	111402D	111402E
<b>Model Name</b>	2D-25L (DT) MFS HEPA			
<b>Type (Powerhead)</b>	Electric	Electric	Electric	Electric
<b>Voltage</b>	230 V	230 V	230 V	230 V
<b>Hertz</b>	50 Hz	50 Hz	50 Hz	50 Hz
<b>Phase</b>	Single	Single	Single	Single
<b>Wattage</b>	1200 W	1200 W	1200 W	1200 W
<b>Power</b>	1.2 kW	1.2 kW	1.2 kW	1.2 kW
<b>Amperage</b>	5 amps.	5 amps.	5 amps.	5 amps.
<b>Air Flow</b>	153 m <sup>3</sup> /h			
<b>Vacuum Pressure</b>	2030 mm H <sub>2</sub> O			
<b>Sound Level</b>	75 dB(A)	75 dB(A)	75 dB(A)	75 dB(A)
<b>Plug Type</b>	European	UK	Swiss	Chinese
<b>Suction Inlet</b>	50 mm	50 mm	50 mm	50 mm
<b>Cart Type</b>	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Filter Shaker (MFS)			
<b>Dry Recovery - Tank</b>	24.6 L	24.6 L	24.6 L	24.6 L
<b>Length</b>	58 cm	58 cm	58 cm	58 cm
<b>Width</b>	53 cm	53 cm	53 cm	53 cm
<b>Weight (Vacuum Only)</b>	23 kg.	23 kg.	23 kg.	23 kg.
<b>Height</b>	100 cm	100 cm	100 cm	100 cm
<b>Cord Length</b>	10.6 m	10.6 m	10.6 m	10.6 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Main Cloth Filter - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38mm) Static Dissipative Tools and Accessories -  
Optional

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



Static  
Dissipating



HEPA -  
Included



Detachable  
Tank



Dry Recovery



SS 430



High Efficiency

## Specifications for 2D-25L (DT) MFS HEPA

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
2D-25L (DT) MFS HEPA	111402B	230 V	50 Hz	Single	1200 W	1.2 kW	5 amps.	153 m <sup>3</sup> /h	2030 mm H <sub>2</sub> O	European	24.6 L
	Dimensions: H100 cm x W53 cm x L58 cm    Weight: 23 kg.    Sound Level: 75 dB(A)										
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											
2D-25L (DT) MFS HEPA	111402C	230 V	50 Hz	Single	1200 W	1.2 kW	5 amps.	153 m <sup>3</sup> /h	2030 mm H <sub>2</sub> O	UK	24.6 L
	Dimensions: H100 cm x W53 cm x L58 cm    Weight: 23 kg.    Sound Level: 75 dB(A)										
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											
2D-25L (DT) MFS HEPA	111402D	230 V	50 Hz	Single	1200 W	1.2 kW	5 amps.	153 m <sup>3</sup> /h	2030 mm H <sub>2</sub> O	Swiss	24.6 L
	Dimensions: H100 cm x W53 cm x L58 cm    Weight: 23 kg.    Sound Level: 75 dB(A)										
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											
2D-25L (DT) MFS HEPA	111402E	230 V	50 Hz	Single	1200 W	1.2 kW	5 amps.	153 m <sup>3</sup> /h	2030 mm H <sub>2</sub> O	Chinese	24.6 L
	Dimensions: H100 cm x W53 cm x L58 cm    Weight: 23 kg.    Sound Level: 75 dB(A)										
Description: Manufacturer motor performance only on an orifice of Ø2" (Ø50mm). Results may vary.											

Please note that specifications are subject to change without notice

## Technical Sheet for 2D-25L (DT) MFS HEPA

### HEPA FILTER AND ACCESSORIES - Included

Part #	Description
212304B	HEPA FILTER (H14)

### FILTERS AND ACCESSORIES - Included

Part #	Description
214883AT	MAIN FILTER ASSMBLY PTFE 2D/AV-20(DT) w/GASKET, RING & LACES(NO CAGE)(PRE-FILTER NO LONGER REQUIRED)
214880B	WIRE CAGE FOR FILTER -POWDER COATED

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
214987	POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)

213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)
--------	--

### TOOLS AND ACCESSORIES - Optional

Part #	Description
383438-50	CRUSHPROOF SUCTION HOSE, BLACK STATIC CONDUCTIVE (NO WIRE), Ø1.5" (Ø38mm) x 50'
383434	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383436	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383435	EXPANDER HOSE CUFF Ø1.5"(38mm) TO Ø2"(Ø50mm) STATIC CONDUCTIVE -BLACK
500175	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM