

Characteristics



HEPA - Included



High Efficiency



Detachable Tank



Dry Recovery



Dual Motor



- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001 H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- For general housekeeping
- Dual Bypass/Dual Speed Heavy Duty motors. 2000 watts (2400 maximum)
- Manual Filter Shaker (MFS) system.
- For dry recovery only
- Stainless Steel Type 430 body and recovery tank.
- Detachable Recovery Tank (DT) for easy disposal of recovered materials
- Equipped with a 4-Wheel cart and tool basket. Cart has SD* conductive wheels

Specifications

4D-25L (DT) MFS HEPA	111415B
Model Name	4D-25L (DT) MFS HEPA
Type (Powerhead)	Electric
Voltage	240 V
Hertz	50 Hz
Phase	Single
Wattage	2100 W
Power	2.1 kW
Amperage	10 amps.
Air Flow	340 m ³ /h
Vacuum Pressure	2290 mm H ₂ O
Sound Level	78 dB(A)
Plug Type	Not Included
Suction Inlet	50 mm
Cart Type	Detachable Tank (DT)
Filter Cleaning	Manual Filter Shaker (MFS)
Dry Recovery - Tank	24.6 L
Length	58 cm
Width	53 cm
Weight (Vacuum Only)	34 kg.
Height	100 cm
Cord Length	10.6 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38mm) Static Dissipative Tools and Accessories - Optional

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



HEPA -
Included



High Efficiency



Detachable
Tank



Dry Recovery



Dual Motor

Specifications for 4D-25L (DT) MFS HEPA

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
4D-25L (DT) MFS HEPA	111415B	240 V	50 Hz	Single	2100 W	2.1 kW	10 amps.	340 m ³ /h	2290 mm H ₂ O	Not Included	24.6 L
Dimensions: H100 cm x W53 cm x L58 cm Weight: 34 kg. Sound Level: 78 dB(A)											

Please note that specifications are subject to change without notice

Technical Sheet for 4D-25L (DT) MFS HEPA

HEPA FILTER AND ACCESSORIES - Included

Part #	Description
215983	HEPA FILTER (MID HEIGHT), 6.375" x 7.40" HIGH w/GASKET, 99.995% EFFICIENCY ON 0.3 MICRON (H14)

FILTERS AND ACCESSORIES - Included

Part #	Description
214883AT	MAIN FILTER ASSMBLY PTFE 2D/AV-20(DT) w/GASKET, RING & LACES(NO CAGE)(PRE-FILTER NO LONGER REQUIRED)
214880B	WIRE CAGE FOR FILTER -POWDER COATED

FILTERS AND ACCESSORIES - Optional

Part #	Description
218095	POLYESTER SAFETY FILTER ASSEMBLY w/CLAMP FOR 4D (FITS AROUND HEPA HOUSING #218093B)

POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
214987	POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

TOOLS AND ACCESSORIES - Optional

Part #	Description
383438-50	CRUSHPROOF SUCTION HOSE, BLACK STATIC CONDUCTIVE (NO WIRE),Ø1.5" (Ø38mm) x 50'
383434	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383436	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383435	EXPANDER HOSE CUFF Ø1.5"(38mm) TO Ø2"(Ø50mm) STATIC CONDUCTIVE -BLACK
500175	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING