

## Characteristics



HEPA - Included



High Efficiency



Detachable Tank



Dry Recovery



Dual Motor



- HEPA Filter - Included with an efficiency of 99.995% on 0.3 micron. Tested: IEST RP-CC001 H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak Tested before leaving our facility.
- For general housekeeping
- Dual Bypass/Dual Speed Heavy Duty motors. 2000 watts (2400 maximum)
- Manual Reverse Purge (MRP) with SD\* Reverse Purge Cartridge.
- For dry recovery only
- Stainless Steel Type 430 body and recovery tank.
- Detachable Recovery Tank (DT) for easy disposal of recovered materials
- Equipped with a 4-Wheel cart and tool basket. Cart has SD\* conductive wheels

## Specifications

4D-25L (DT) MRP HEPA	111931B
<b>Model Name</b>	4D-25L (DT) MRP HEPA
<b>Type (Powerhead)</b>	Electric
<b>Voltage</b>	240 V
<b>Hertz</b>	50 Hz
<b>Phase</b>	Single
<b>Wattage</b>	2100 W
<b>Power</b>	2.1 kW
<b>Amperage</b>	10 amps.
<b>Air Flow</b>	340 m <sup>3</sup> /h
<b>Vacuum Pressure</b>	2290 mm H <sub>2</sub> O
<b>Sound Level</b>	78 dB(A)
<b>Plug Type</b>	Not Included
<b>Suction Inlet</b>	50 mm
<b>Cart Type</b>	Detachable Tank (DT)
<b>Filter Cleaning</b>	Manual Reverse Purge (MRP)
<b>Dry Recovery - Tank</b>	25 L
<b>Length</b>	58 cm
<b>Width</b>	53 cm
<b>Weight (Vacuum Only)</b>	34 kg.
<b>Height</b>	100 cm
<b>Cord Length</b>	10.6 m

Please note that specifications are subject to change without notice

## Use only recommended tools & accessories



25L Detachable Tank



HEPA Filter - Included



Conductive Aluminized Spun Bond Reverse Purge Cartridge  
(shown with and without optional skirt) - Included



Clear Polyliner Recovery Bags - Optional



Ø1.5" (Ø38mm) Static Dissipative Tools and Accessories -  
Optional

### European Headquarters

**Tiger-Vac Europa S.R.L.**  
Via Marie Curie 17  
Zona Industriale Ponte Rizzoli  
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)  
Fax: ((39) 051 4695077)  
Website: <http://www.tiger-vac.eu>  
Email: [info@tiger-vac.it](mailto:info@tiger-vac.it)

### International Headquarters

**Tiger-Vac International Inc.**  
2020 Dagenais Blvd. Ouest  
Laval, Quebec  
Canada H7L 5W2

Tel: (450-625-0099)  
Fax: (450-625-3388)  
Website: <http://www.tiger-vac.com>  
Email: [sales@tiger-vac.com](mailto:sales@tiger-vac.com)



HEPA - Included



High Efficiency



Detachable Tank



Dry Recovery



Dual Motor

## Specifications for 4D-25L (DT) MRP HEPA

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
<b>4D-25L (DT) MRP HEPA</b>	<b>111931B</b>	240 V	50 Hz	Single	2100 W	2.1 kW	10 amps.	340 m <sup>3</sup> /h	2290 mm H <sub>2</sub> O	Not Included	25 L
Dimensions: H100 cm x W53 cm x L58 cm    Weight: 34 kg.    Sound Level: 78 dB(A)											

Please note that specifications are subject to change without notice

## Technical Sheet for 4D-25L (DT) MRP HEPA

### HEPA FILTER AND ACCESSORIES - Included

Part #	Description
215983	HEPA FILTER (MID HEIGHT), 6.375" x 7.40" HIGH w/GASKET, 99.995% EFFICIENCY ON 0.3 MICRON (H14)

### REVERSE PURGE FILTER CARTRIDGE - Included

Part #	Description
214182A	FILTER CARTRIDGE, ALUMINIZED SPUN BOND POLYESTER, 16"H x 3.63"ID x 7.932"OD, 1" PLEATS, 13 SQ.FT

### FILTERS AND ACCESSORIES - Optional

Part #	Description
218095	POLYESTER SAFETY FILTER ASSEMBLY w/CLAMP FOR 4D (FITS AROUND HEPA HOUSING #218093B)

### POLY LINER RECOVERY BAGS AND ACCESSORIES - Optional

Part #	Description
214987	POLY LINER -CLEAR WITH DRAW STRING (PACKAGE OF 5)
213780	POLY LINER RETAINER PLATE ASSEMBLY (FOR USE WITH MOTORS UP TO 5HP)

### TOOLS AND ACCESSORIES - Optional

Part #	Description
383438-50	CRUSHPROOF SUCTION HOSE, BLACK STATIC CONDUCTIVE (NO WIRE), Ø1.5" (Ø38mm) x 50'
383434	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383436	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK
383435	EXPANDER HOSE CUFF Ø1.5"(38mm) TO Ø2"(Ø50mm) STATIC CONDUCTIVE -BLACK
500175	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING